



SIXTY-SIX SERIES

2008

	66 ATA	66 RC3	66 RCV	
TRAVEL	140 MM-180 MM Adjustable	180 MM	180 MM	
WEIGHTS	2390g/ 5.93 lbs.	2705g/ 5.96 lbs.	2950g/ 6.5 lbs.	
LT. INTERNAL	RC3	RC3	RV	
RT. INTERNAL	ATA	Mech. PL	CV	
LEFT ADJUSTMENT FEATURES	Rebound Auto Hi-Lo Compression Adjust	Air Preload Rebound Auto Hi-Lo Compression Adjust	Air Preload Rebound Piston Rod	
RIGHT ADJUSTMENT FEATURES	Air Travel Adjust Pos. and Neg. Air Progressive Air	Mech. Preload	Air Preload Compression Piston Rod	
SPRING TYPE	Air	1 Side Coil	Coil	
CASTING AND STANCHION	38mm New 20mm QR Axle Nickel Coated Stanchion Tubes	38mm New 20mm QR Axle Aluminum Stanchion Tubes	38mm New 20mm QR Axle Aluminum Stanchion Tubes	
STEER TUBE	Aluminum Reinforced	Aluminum Reinforced	Steel	
BRAKE SYSTEM	8" Post Mount (9" Maximum)	8" Post Mount (9" Maximum)	8" Post Mount (9" Maximum)	
OPTIONS	1.5" Aluminum Steer Tube	1.5" Aluminum Steer Tube	1 1/8" or 1.5" Aluminum Steer Tube	
MANUFACTURED	Taiwan	Taiwan	Taiwan	

The 66 was inspired by countless runs in Whistler's MTB park and the desire to have a lightweight, long travel single crown fork with 888 performance. The 66 is the single crown benchmark that all suspension companies try to duplicate.

FEATURED TECHNOLOGY

ATA- AIR TRAVEL ADJUST

ETA- EXTENSION TRAVEL ADJUST

RC3- REBOUND COMPRESSION

ATA2- AIR TRAVEL ADJUST 2



NEW QR AXLE

