



Active suspension, with big bump capability because the damping and after months of testing we accomplished our goal. In addition, we developed an industry first to offer a rear shock that was easily serviceable without the need to send it back to the manufacturer or a main service center.

ROCO REAR SHOCK

2008



	ROCO AIR RC WORLD CUP	ROCO AIR TST R	ROCO AIR R W/ PIGGY BACK	ROCO 3PL	
FEATURES	Ext. adjustable Trail Selection Technology (TST) Ext. adj. -145mm Ext. adjustable bottom-out resistance via air valve Adj. Air Spring Nickel Coated Air Cartridge High Volume Linear Air Spring	Ext. adjustable Trail Selection Technology (TST) Ext. adj. Rebound Ext. adjustable bottom-out resistance via air valve Adj. Air Spring Nickel Coated Air Cartridge High Volume Linear Air Spring	Ext. adj. Rebound Ext. adjustable bottom-out resistance via air valve Adj. Air Spring Nickel Coated Air Cartridge High Volume Linear Air Spring	3 Position Lock Up Adj. Air Spring Nickel Coated Air Cartridge High Volume Linear Air Spring External Rebound Adjustment	
SIZES	9.5" x 3" 241.3mm x 76.2mm 8.75" x 2.75" 220mm x 70mm 8.5" x 2.5" 215.9mm x 63.5mm 7.88" x 2.25" 200mm x 57mm 7.5" x 2.0" 190.5mm x 50mm	9.5" x 3" 241.3mm x 76.2mm 8.75" x 2.75" 220mm x 70mm 8.5" x 2.5" 215.9mm x 63.5mm 7.88" x 2.25" 200mm x 57mm 7.5" x 2.0" 190.5mm x 50mm	9.5" x 3" 241.3mm x 76.2mm 8.75" x 2.75" 220mm x 70mm 8.5" x 2.5" 215.9mm x 63.5mm 7.88" x 2.25" 200mm x 57mm 7.5" x 2.0" 190.5mm x 50mm	8.5" x 2.5" 215.9mm x 63.5mm 8.0" x 2.25" 200mm x 57mm 7.5" x 2.0" 190.5mm x 50mm 6.5" x 1.5" 165.1mm x 38.1mm 6.0" x 1.25" 152.4mm x 31.8mm	
MANUFACTURED	Italy	Italy	Italy	Italy	

FEATURED TECHNOLOGY

TST - TRAILAIN SELECTION TECHNOLOGY

